# SDS SAFETY DATA SHEET ESGARD



# **ESGARD HEAVY DUTY GEAR & PINION LUBE**

#### PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: ESGARD HEAVY DUTY GEAR & PINION LUBE

515 DEBONNAIRE ROAD

SCOTT, LOUISIANA 70583

SDS Number: ESGARD HD G & P L V.1

**Product Code:** 1100-043 **Revision Date:** 2/16/2016

Version: 1

CAS Number: 64742-52-5; 61789-86-4
Chemical Formula: PROPRIETARY \*\*\*
Product Use: RUST INHIBITIVE COATING

Supplier Details: ESGARD Vendor Details: ESGARD

515 DEBONNAIRE ROAD SCOTT, LOUISIANA 70583

Contact: ROBERT SAWVEL (PRESIDENT) Contact: RUSSELL BREAUX (SALES)

 Phone:
 337-234-6327
 Phone:
 337-234-6327

 Fax:
 337-234-0113
 Fax:
 337-234-0113

 Email:
 ROBERT@ESGARD.COM
 Email:
 RUSSELL@ESGARD.COM

 Web:
 HTTPS://WWW.ESGARD.COM
 Web:
 HTTPS://WWW.ESGARD.COM

**HAZMAT & 24 HOUR CONTACT INFORMATION** 

CHEMTREC - 1 (800) 424-9300

2

#### HAZARDS IDENTIFICATION

#### Classification of the Substance or Mixture

GHS Classification in Accordance with 29 CFR 1910 (OSHA HCS):

Health, Skin sensitization, 1

**GHS Label Elements, Including Precautionary Statements** 

GHS Signal Word: WARNING
GHS Hazard Pictograms:



#### **GHS Hazard Statements:**

H317 - May cause an allergic skin reaction

#### **GHS Precautionary Statements:**

P102 - Keep out of reach of children.

P210 - Keep away from heat/sparks/open flames/hot surfaces. No smoking

P404 - Store in a closed container.

P411 - Store at temperatures not exceeding 100°F (35° C)

## Hazards not Otherwise Classified (HNOC) or not Covered by GHS

**Inhalation:** Significant levels of vapor not likely to occur with normal use of product.

**Eye Contact:** May cause irritation.

# 3 COMPOSITION/INFORMATION ON INGREDIENTS

#### Ingredients:

SDS Number: ESGARD HD G & P L V.1 Page 1 of 4 Revision Date: 2/16/2016

FIRST AID MEASURES

**Inhalation:** Not a direct hazard if product is applied as recommended and used for intended purposes. If respiratory symptoms

should develop move personnel away from source of exposure and into fresh air. If symptoms persist seek medical

attention.

Skin Contact: Wipe excess material from skin with a cloth. Wash contaminated area of skin with a waterless skin cleanser once all

product is removed wash with soap and water. Should a waterless skin cleanser not be available wash skin for a

minimum of 15 minutes with soap and water.

**Eye Contact:** Flush with large amounts of water for a minimum of 15 minutes. If irritation persists seek medical attention.

Ingestion: Not a direct hazard if product is applied as recommended and used for intended purposes. If ingestion should occur

seek medical attention.

# 5 FIRE FIGHTING MEASURES

Flammability: Will not burn unless preheated.

Flash Point: 455° F (235° C) PMCC

Flash Point Method: Pensky-Martens Closed Cup Test

Extinguishing Media: Extinguish with dry chemical, CO2, water spray, foam, sand, and/or earth. Water and

foam may cause frothing.

**Special Considerations:** Fire fighters should enter area wearing positive pressure respiratory protection.

#### ACCIDENTAL RELEASE MEASURES

Personal Precautions: No action should be taken that may involve personal risk. In the event of a spill immediately contact

upper management for final instructions. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled materials. No smoking. Shut off and keep spilled product away from all possible ignition sources. Avoid breathing and vapor or mist that may be produced. Ensure proper ventilation. Don appropriate personal protective equipment before proceeding with any cleanup

(See section 8).

**Environmental Precautions:** Avoid dispersal of spilled material and runoff from contacting soil, waterways, drains, and sewers.

Inform all relevant authorities if the product has caused environmental pollution to sewers, waterways,

soil, air, etc.

**Spill containment and clean up:** Consult with management or proper authority to determine if cleanup may be conducted safely.

Avoid the use of any high powered or jet water stream that may spread the product. After donning proper personal protective equipment (See section 8) transfer bulk of material into another container. Dilute with water and mop up if product is water-soluble if not absorb any remaining residue with proper absorbents such as earth or vermiculite. Do not use any combustible material as an absorbent. Sweep up and dispose of as solid waste in accordance with applicable federal, state, and local regulations. Contact a certified/licensed waste disposal company for proper disposal of waste. Absorbent material

may pose the same hazard (if any) as the spilled product.

See Section 1 for emergency contact information and Section 13 for waste disposal.

#### 7 HANDLING AND STORAGE

Handling Precautions: Avoid contact with skin and eyes. Observe good standards of industrial hygiene. Keep away from

sources of ignition.

Storage Requirements: Storage Temperature: 0-100°F ( -18 -35° C )

Storage Precautions: Keep in closed containers.

## 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

SDS Number: ESGARD HD G & P L V.1 Page 2 of 4 Revision Date: 2/16/2016

**Engineering Controls:** Provide forced air ventilation when applying in confined spaces.

**Personal Protective** 

HMIS PP, C | Safety Glasses, Gloves, Apron

**Equipment:** Respiratory Protection: Unlikely to be necessary. Use approved chemical filter respirator.

Eyes: Use of safety glasses or chemical eye goggles is suggested. Hands: Use of non-natural and non-butyl rubber gloves is recommended.

Skin: Use protective clothing. Use of pants, long sleeve shirt, and apron recommended when applying

product

**Exposure Limits:** Not determined.

Always pratice good hygiene. Remember chemicals can transfer from your hands to things that may cause ingestion of product, e.g., food, cigarettes, etc. Always wash hands and skin thoroughly after coming into contact with product even if proper personal protective equipment was used.

# 9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Light black

Physical State: Grease

Physical State: Grease
Spec Grav./Density: (25°C): 1.35-1.40
Boiling Point: > 300°F (148°C)
Vapor Pressure: Not determined
pH: 7.5

Odor: Mild Odor
Solubility: Not water soluble
Freezing/Melting Pt.: Not determined
Flash Point: 455°F (235°C) PMCC

# 10 STABILITY AND REACTIVITY

Chemical Stability: Product is stable under normal conditions.

Conditions to Avoid: Exposed flames; high temperature sources; strong oxidizers

Materials to Avoid: Strong Oxidizing Agents.

Hazardous Decomposition: Combustion can produce a variety of compounds including oxides of sulfur, oxides of carbon, water

vapor, and unidentified organic and inorganic compounds - some of which may be toxic.

Hazardous Polymerization: Will not occur.

#### 11 TOXICOLOGICAL INFORMATION

LD50 (Animal/Oral): No data available

Possible Health Effects: Eves - Mildly irritating

Skin - Prolonged contact may cause skin irritation

Inhalation - Product is unlikely to present any significant hazard during normal of product use at ambient temperature. Should product be sprayed and inhaled due to the lack of personal protective gear or proper ventilation pulmonary abnormalities could occur.

Ingestion - Ingestion of this product is not a health hazard likely to arise when using and applying product correctly and for intended use.

# 12 ECOLOGICAL INFORMATION

No data available

## 13 DISPOSAL CONSIDERATIONS

Product, waste, and any materials that may have been used if a spill occurred should be disposed of via an authorized waste disposal contractor in accordance with all local, state, and federal regulations. You may call Esgard to discuss the possibility of returning waste, expired product, and contanimated materials to Esgard for a fee.

# 14 TRANSPORT INFORMATION

Non-hazardous for air, sea, and road freight.

**Shipping Information:** Rust Preventative Coating, Non-Hazardous, Class 65 (Shipping Class)

**Export Code:** 3403.19.5000

SDS Number: ESGARD HD G & P L V.1 Page 3 of 4 Revision Date: 2/16/2016

#### 15

#### REGULATORY INFORMATION

Component (CAS#) [%] - CODES

Mineral Oil, petroleum Distillates, Hydrotreated (mild) Heavy Naphthenic (64742-52-5) [10-20%] NJHS, TSCA

Sulfonic acids, petroleum, calcium salts (61789-86-4) [02-10%] TSCA

Regulatory CODE Descriptions

NJHS = NJ Right-to-Know Hazardous Substances

TSCA - Toxic Substances Control Act

TSCA = Toxic Substances Control Act

#### 16

#### OTHER INFORMATION

NFPA: Health = 1, Fire = 0, Reactivity = 0, Specific Hazard = None

HMIS III: Health = 1, Fire = 0, Physical Hazard = 0 HMIS PPE: C - Safety Glasses, Gloves, Apron







**General Safety:** Anyone can fall into a container and drown - drowning can occur in a very small amount of water or product that covers the mouth and/or nose. Keep product out of reach of children and dispose of container properly (as discussed in section 13) when empty or there is no longer a need for the use of this product.

Do not mix with other chemicals

This data sheet does not constitute as an assessment of the workplace risks as required under the provisions of the Health & Safety at Work Act and the Control of Substances Hazardous to Health. (COSHH)

## Disclaimer:

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose(s).

All information contained within this data sheet is not claiming characteristics of the product in term of legal claims of performance / guarantee.

All information contained within this data sheet only describes safety measures and no liability may arise from the use or application of the product described herein.

All information contained within this data sheet is given in good faith and based on our current knowledge of the product.

**Author:** Ciji Thibodeaux

Publication Date: February 16, 2016

**Revision No.:** 0